

MATERIAL SAFETY DATA SHEET

Prepared to U.S. OSHA, CMA, ANSI, and Canadian WHMIS

PART I What is the material and what do I need to know in an emergency?

1. PRODUCT IDENTIFICATION

TRADE NAME/MATERIAL NAME: Metronidazole Cream 0.75%

DESCRIPTION:	Metronidazole Cream
NDC #:	0168-0323-46
CHEMICAL NAME (for active ingredient):	2-Methyl-5-nitroimidazole-1-ethanol
CHEMICAL FAMILY (for active ingredient):	Nitroimidazole
HOW SUPPLIED:	0.75% Cream
FORMULA (for active ingredient):	C ₆ H ₉ N ₃ O ₃
PRODUCT USE:	Pharmaceutical for Human Use
SUPPLIER/MANUFACTURER'S NAME:	FOUGERA PHARMACEUTICALS INC.
ADDRESS:	60 Baylis Road Melville, NY 11747
BUSINESS PHONE/GENERAL MSDS INFORMATION:	1-631-454-7677
EMERGENCY PHONE (U.S./Canada/Puerto Rico):	1-800-424-9300 (24-hr)
EMERGENCY PHONE (OUTSIDE U.S.):	+1-631-454-7677

NOTE: ALL United States Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalent Standards, and Canadian WHMIS [Controlled Products Regulations] required information is included in appropriate sections based on the U.S. ANSI Z400.1-2004 format. This product has been classified in accordance with the hazard criteria of the countries listed above.

2. HAZARD IDENTIFICATION

EMERGENCY OVERVIEW: Product Description: This product is a slightly white to slightly yellow, odorless cream.
Health Hazards: The chief health hazard associated with exposure during normal use and handling is the potential for irritation of contaminated skin. Metronidazole, the active ingredient in this product, is a potential carcinogen, based on animal data. Individuals who have had allergic reactions to products containing the active ingredient, Metronidazole, or any other components of this product may experience allergic reactions following use or exposure.
Flammability Hazards: If heated to high temperatures for a prolonged period, the water in this product can evaporate off and the residue may ignite. When involved in a fire, this material may decompose and produce irritating vapors and toxic compounds (including carbon oxides and nitrogen oxides).
Reactivity Hazards: This product is not reactive.
Environmental Hazards: This product has not been tested for environmental effects. Large quantities released to the aquatic and terrestrial environment may have an adverse effect.
Emergency Considerations: Emergency responders should wear appropriate protection for situation to which they respond.

3. COMPOSITION and INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS #	% w/w
Metronidazole	443-48-1	0.75%
Benzyl Alcohol	100-51-6	Proprietary
Cetearyl Alcohol	67762-27-0	Proprietary
Glycerin	56-81-5	Proprietary
Isopropyl Palmitate	142-91-6	Proprietary
Polysorbate 60	9005-67-8	Proprietary
Sorbitol	50-70-4	Proprietary
Water and other components. Each of the other components is present in less than 1 percent concentration (0.1% concentration for potential carcinogens, reproductive toxins, respiratory tract sensitizers, and mutagens).	The remaining components do not contribute any significant additional hazards.	Balance

PART II What should I do if a hazardous situation occurs?

4 FIRST-AID MEASURES

Persons developing hypersensitivity reactions should receive medical attention. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Take a copy of label and MSDS to physician or health professional with the contaminated individual.

SKIN EXPOSURE: If adverse skin effects occur, discontinue use. Seek medical attention.

EYE EXPOSURE: If this product contaminates the eyes, rinse eyes under gently running water. Use sufficient force to open eyelids and then "roll" eyes while flushing. Minimum flushing is for 15 minutes. The contaminated individual must seek medical attention if any adverse effect continues after rinsing.

INHALATION: If vapors of this product are inhaled, causing irritation, remove victim to fresh air. If necessary, use artificial respiration to support vital functions.

4 FIRST-AID MEASURES (Continued)

INGESTION: If this product is swallowed, CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION. If professional advice is not available, do not induce vomiting. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or unable to swallow. If victim is convulsing, maintain an open airway and obtain immediate medical attention.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Pre-existing skin conditions and blood dyscrasia may be aggravated by repeated overexposures to this product.

RECOMMENDATIONS TO PHYSICIANS: This product should only be given to patients by persons experienced in management of patients receiving the type of therapy intended for this product. Treat symptoms and eliminate exposure.

5. FIRE-FIGHTING MEASURES

FLASH POINT: Not applicable.

AUTOIGNITION TEMPERATURE: Not applicable.

FLAMMABLE LIMITS (in air by volume, %): Not applicable.

FIRE EXTINGUISHING MEDIA: Use extinguishing media appropriate for surrounding fire.


UNSUITABLE FIRE EXTINGUISHING MEDIA: None known.

SPECIAL FIRE AND EXPLOSION HAZARDS: If heated to high temperatures for a prolonged period, the water in this product can evaporate off and the residue may ignite. When involved in a fire, this material may decompose and produce irritating vapors and toxic compounds (including carbon oxides and nitrogen oxides). This product contains known and suspect skin sensitizers so presents a contact hazard to firefighters.

Explosion Sensitivity to Mechanical Impact: Not sensitive.

Explosion Sensitivity to Static Discharge: Not sensitive.

ADVICE TO FIRE-FIGHTERS: Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus (SCBA) and full protective equipment. If protective equipment is contaminated by this product, it should be thoroughly washed with running water prior to removal of SCBA respiratory protection. Firefighters whose protective equipment becomes contaminated should thoroughly shower with warm, soapy water and should receive medical evaluation if they experience any adverse effects.



6. ACCIDENTAL RELEASE MEASURES

SPILL AND LEAK RESPONSE: Proper protective equipment should be used. In the event of a spill, clear the area and protect people. The atmosphere must have levels of components lower than those listed in Section 8, (Exposure Controls and Personal Protective Equipment) if applicable, and have at least 19.5 percent oxygen before personnel can be allowed into the area without Self-Contained Breathing Apparatus (SCBA).

Small Spills: Wear goggles and gloves while wiping up small spills of this product with polypad or sponge.

Large Spills: Trained personnel following pre-planned procedures should handle non-incident releases. Access to the spill areas should be restricted. Protective apparel should be used with a respirator when there is any danger of mists or sprays being generated. Minimum Personal Protective Equipment should be rubber gloves, rubber boots, face shield, and Tyvek suit. Dispersing mists or sprays into surrounding air and possibly inhaling them is a serious matter and should be treated as such. Minimum level of personal protective equipment for releases in which the level of oxygen is less than 19.5% or is unknown must be **Level B: triple-gloves (rubber gloves and nitrile gloves over latex gloves), chemical resistant suit and boots, hard hat, and Self-Contained Breathing Apparatus**. Absorb spilled liquid using polypads or other suitable absorbent material. Prevent material from entering sewer or confined spaces, waterways, soil or public waters. Monitor area and confirm levels are below exposure limits given in Section 8 (Exposure Controls-Personal Protection), if applicable, before non-response personnel are allowed into the spill area.

Decontaminate the area of the spill thoroughly using detergent and water. Place all spill residue in an appropriate container and seal. Dispose of in accordance with applicable Federal, State, and local procedures (see Section 13, Disposal Considerations).

PART III *How can I prevent hazardous situations from occurring?*

7. HANDLING and USE

WORK PRACTICES AND HYGIENE PRACTICES: As with all chemicals, avoid getting this product ON YOU or IN YOU. Do not eat, drink, smoke, or apply cosmetics while handling this product. Wash hands thoroughly after handling this product or equipment and containers that contain this product. Follow SPECIFIC USE INSTRUCTIONS supplied with this product. Particular care in working with this product must be practiced in pharmacies and other preparation areas, during manufacture of this product, and during patient administration.

STORAGE AND HANDLING PRACTICES: Employees must be trained to properly use this product. Use of this product should be performed in a designated area for working with drugs. Ensure product is properly labeled. Store this product away from incompatible materials. Store this product in original container.

7. HANDLING and USE (Continued)

PRODUCT PREPARATION INSTRUCTIONS FOR MEDICAL PERSONNEL: Handle this material following standard medical practices and following the recommendations presented on the Package Insert.

SPECIFIC USE(S): This product is a human pharmaceutical. Follow all industry standards for use of this product.

PROTECTIVE PRACTICES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT: When cleaning non-disposable equipment, wear latex or butyl rubber (double gloving is recommended), goggles, and lab coat. Wash equipment with soap and water. Wipe equipment down with damp sponge or polypad. Collect all rinsates and dispose of according to applicable U.S. Federal, State, and local hazardous waste disposal regulations or waste disposal regulations of Canada. All disposable items contaminated with this product should be disposed of properly.

8. EXPOSURE CONTROLS - PERSONAL PROTECTION

VENTILATION AND ENGINEERING CONTROLS: Use with adequate ventilation. Follow standard medical product handling procedures. During decontamination of work surfaces, workers should wear the same equipment recommended in Section 6 (Accidental Release Measures) of this MSDS.

EXPOSURE LIMITS/GUIDELINES:

CHEMICAL NAME	CAS #	EXPOSURE LIMITS IN AIR							OTHER	
		ACGIH-TLVs		OSHA-PELs		NIOSH-RELS		NIOSH IDLH		
		TWA mg/m ³	STEL mg/m ³	TWA mg/m ³	STEL mg/m ³	TWA mg/m ³	STEL mg/m ³			
Benzyl Alcohol	100-51-6	NE	NE	NE	NE	NE	NE	NE	AIHA WEELs: TWA = 10 ppm	
Cetearyl Alcohol	67762-27-0	NE	NE	NE	NE	NE	NE	NE	NE	
Glycerin	56-81-5	10 (mist); NIC: Withdraw TLV	NE	15 (total dust) 5 (resp. fraction) 10 (total) 5 (resp. fraction) [vacated 1989 PEL]	NE	NE	NE	NE	NE	DFG MAKs: TWA = 50 (Inhalable fraction) PEAK = 2•MAK 15 min, average value, 1-hr interval, 4 per shift DFG MAK Pregnancy Risk Classification: C
Isopropyl Palmitate	142-91-6	NE	NE	NE	NE	NE	NE	NE	NE	
Metronidazole	443-48-1	NE	NE	NE	NE	NE	NE	NE	NE	
Polysorbate 60	9005-67-8	NE	NE	NE	NE	NE	NE	NE	NE	
Sorbitol	50-70-4	NE	NE	NE	NE	NE	NE	NE	NE	

NE = Not Established NIC = Notice of Intended Change See Section 16 for Definitions of Terms Used.

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132) or equivalent standards of Canada (including CSA Standard Z94.4-02 and CSA Standard Z94.3-07). Please reference applicable regulations and standards for relevant details.

RESPIRATORY PROTECTION: A respirator is not required for routine conditions of use of this product. If respiratory protection is needed, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, or Canadian CSA Standard Z94.4-02. Oxygen levels below 19.5% are considered IDLH by OSHA. In such atmospheres, use of a full-facepiece pressure/demand SCBA or a full facepiece, supplied air respirator with auxiliary self-contained air supply is required under OSHA's Respiratory Protection Standard (1910.134-1998).

EYE PROTECTION: Not normally needed during normal use. If necessary, refer to U.S. OSHA 29 CFR 1910.133 or Canadian CSA Standard Z94.3-07.

HAND PROTECTION: For situations in which prolonged skin contact is anticipated, double glove, using latex, nitrile, or rubber gloves. Check gloves for leaks. Wash hands before putting on gloves and after removing gloves. Gloves should cover the gown cuff. If necessary, refer to U.S. OSHA 29 CFR 1910.138 or appropriate standards of Canada.

BODY PROTECTION: During patient administration, use of lightweight cotton gown or other medical attire is recommended. If a hazard of injury to the feet exists due to falling objects, rolling objects, where objects may pierce the soles of the feet or where employee's feet may be exposed to electrical hazards, use foot protection, as described in U.S. OSHA 29 CFR 1910.136 and the Canadian CSA Standard Z195-02, *Protective Footwear*.

9. PHYSICAL and CHEMICAL PROPERTIES

BOILING POINT: Not established.

FREEZING/MELTING POINT: Not established.

EVAPORATION RATE (nBuAc = 1): Not established.

SOLUBILITY IN WATER: Slightly soluble.

VAPOR PRESSURE (air = 1): Not established.

SPECIFIC GRAVITY @ 50°C (water = 1): Approx. 0.94

ODOR THRESHOLD: Not established.

pH: 4-6

COEFFICIENT WATER/OIL DISTRIBUTION: Not established.

APPEARANCE AND COLOR: This product is a slightly white to slightly yellow, odorless cream.

HOW TO DETECT THIS SUBSTANCE (warning properties): The appearance of this product is a distinguishing characteristic to identify the product in event of accidental release.

10. STABILITY and REACTIVITY

REACTIVITY/CHEMICAL STABILITY: This product is stable.

DECOMPOSITION PRODUCTS: *Combustion:* If exposed to extremely high temperatures, thermal decomposition may generate irritating fumes and toxic gases (e.g., carbon oxides and nitrogen oxides). *Hydrolysis:* None known.

MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE: This product is generally compatible with other common materials in a medical facility. Acids, caustics, and other chemicals that could affect its performance should be avoided.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Avoid heat, light, and contact with incompatible chemicals.

PART IV *Is there any other useful information about this material?*

11. TOXICOLOGICAL INFORMATION

SYMPTOMS OF OVEREXPOSURE BY ROUTE OF EXPOSURE: The health hazard information provided below is pertinent to medical employees handling this product in an occupational setting. This product is designed for application on the skin. The following paragraphs describe the symptoms of exposure by route of exposure.

INHALATION: Although unlikely due to form of product, inhalation of vapors of this product may slightly irritate the nose, throat, and lungs. Symptoms are generally alleviated upon breathing fresh air.

CONTACT WITH SKIN or EYES: Skin contact can cause mild moderate irritation, which is alleviated upon rinsing with soap and water. Due the presence of Benzyl Alcohol (a weak skin sensitizer) and Cetearyl Alcohol (a suspect skin sensitizer) skin contact may cause an allergic reaction in sensitive individuals; subsequent exposure to very small amounts may cause an allergic reaction in sensitive individuals, with symptoms of redness, itching, welts and irritation. Eye contact may cause mild to moderate irritation, redness, and tearing.

SKIN ABSORPTION: The Benzyl Alcohol component of this product may be absorbed through the skin. Skin absorption is not expected to contribute significantly to overall exposure.

INGESTION: Ingestion is not a significant route of occupational overexposure. Acute ingestion of large quantities of this product or chronic ingestion caused by poor hygiene practices may cause adverse symptoms. Symptoms of ingestion overexposure may include nausea, vomiting, loss of coordination, seizures, muscle weakness, muscle atrophy, pain, and numbness.

INJECTION: Though not anticipated to be a significant route of overexposure for this product, injection (via punctures or lacerations by contaminated objects) may cause redness at the site of injection. Symptoms may include those described for "Ingestion".

GENERAL TOXICITY INFORMATION: Metronidazole, the active ingredient in this product, is a potential carcinogen, based on animal data. Individuals who have had allergic reactions to products containing the active ingredient, Metronidazole, or any other components of this product may experience allergic reactions following use or exposure. Persons using the product in therapeutic doses may experience burning, stinging, swelling, irritation, itching, worsening of rosacea, dryness, transient redness, metallic taste, tingling or numbness of extremities, and nausea.

IRRITANCY OF PRODUCT: This product may irritate contaminated tissue.

SENSITIZATION OF PRODUCT: Due the presence of Benzyl Alcohol (a weak skin sensitizer) and Cetearyl Alcohol (a suspect skin sensitizer) skin contact may cause an allergic reaction in sensitive individuals; subsequent exposure to very small amounts may cause an allergic reaction in sensitive individuals, with symptoms of redness, itching, welts and irritation.

HEALTH EFFECTS OR RISKS FROM EXPOSURE: An Explanation in Lay Terms. Overexposure to this product may cause the following health effects:

Acute: The primary health effects that may be experienced by medical personnel exposed to this product is mild irritation of contaminated skin. Accidental ingestion may cause adverse effects. Although unlikely, inhalation may slightly irritate the respiratory system. Eye contact will cause irritation.

Chronic: Metronidazole, the active ingredient in this product, is a potential carcinogen, based on animal data. Due to the presence of known and potential skin sensitizers, susceptible persons may experience allergic reaction.

TARGET ORGANS:

Acute: Occupational Exposure: Skin, eyes. *Therapeutic Doses:* Skin.

Chronic: Occupational Exposure: Skin. *Therapeutic Doses:* Skin.



HAZARDOUS MATERIAL IDENTIFICATION SYSTEM

HEALTH HAZARD	(BLUE)	2*
----------------------	--------	----

FLAMMABILITY HAZARD	(RED)	0
----------------------------	-------	---

PHYSICAL HAZARD	(YELLOW)	0
------------------------	----------	---

PROTECTIVE EQUIPMENT

EYES	RESPIRATORY	HANDS	BODY
	SEE SECTION 8		SEE SECTION 8

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate
3 = Serious 4 = Severe * = Chronic hazard

For Routine Industrial Use and Handling Applications

11. TOXICOLOGICAL INFORMATION (Continued)

TOXICITY DATA: The toxicity data available for the active component of this product are presented in this MSDS. Additional data are available for the excipient components of this product, but are not presented in this MSDS; Contact Fougera for more information.

METRONIDAZOLE:

Standard Draize Test (Skin-Human) 0.75%/3 weeks-continuous: Mild

TDLo (Oral-Woman) 40 mg/kg: Behavioral: hallucinations, distorted perceptions

TDLo (Oral-Woman) 12 mg/kg: Eye: effect, not otherwise specified, Behavioral: tremor

TDLo (Oral-Man) 3570 µg/kg/day: Liver: jaundice, other or unclassified, other changes; Nutritional and Gross Metabolic: body temperature increase

TDLo (Oral-Woman) 85.8 mg/kg/14 days-intermittent: Gastrointestinal: nausea or vomiting, other changes

TDLo (Oral-Man) 1030 mg/kg/8 weeks: Peripheral Nerve and Sensation: paresthesia, structural change in nerve or sheath

TDLo (Oral-Human) 39,600 mg/kg/4 weeks-intermittent: Peripheral Nerve and Sensation: sensory change involving peripheral nerve Sense Organs and Special Senses (Taste): change in function; Behavioral: headache

TDLo (Intravenous-Woman) 100 mg/kg/5 days: intermittent: Behavioral: hallucinations, distorted perceptions, toxic psychosis, irritability

LD₅₀ (Oral-Rat) 3 g/kg: Behavioral: somnolence (general depressed activity); Lungs, Thorax, or Respiration: cyanosis Nutritional and Gross Metabolic - body temperature decrease

LD₅₀ (Oral-Mouse) 3800 mg/kg: Biochemical: Enzyme inhibition, induction, or change in blood or tissue levels: other oxidoreductases

LD₅₀ (Oral-Mammal) 2074 mg/kg

LD₅₀ (Intraperitoneal-Rat) 870 mg/kg

LD₅₀ (Intraperitoneal-Mammal) 492 mg/kg

LD₅₀ (Subcutaneous-Mouse) 3640 mg/kg: Behavioral: somnolence (general depressed activity), tremor, convulsions or effect on seizure threshold

TDLo (Oral-Rat) 2500 mg/kg: Reproductive: Paternal Effects: testes, epididymis, sperm duct; Related to Chronic Data: changes in testicular weight

TDLo (Oral-Rat) 34 g/kg/34 days-continuous: Kidney/Ureter/Bladder: hematuria; Related to Chronic Data: death, changes in testicular weight

TDLo (Oral-Rat) 219 g/kg/2 years-continuous: Tumorigenic: carcinogenic by RTECS criteria; Liver: tumors Skin and Appendages: tumors

TDLo (Oral-Rat) 16,800 mg/kg: male 42 day(s) pre-mating: Reproductive: Fertility: male fertility index (e.g. # males impregnating females per # males exposed to fertile non-pregnant females)

TDLo (Oral-Rat) 22,400 mg/kg: male 56 day(s) pre-mating: Reproductive: Paternal Effects: spermatogenesis (incl. genetic material, sperm morphology, motility, and count), testes, epididymis, sperm duct

METRONIDAZOLE (continued):

TDLo (Oral-Mouse) 6500 mg/kg/26 days-intermittent: Brain and Coverings: other degenerative changes; Nutritional and Gross Metabolic: weight loss or decreased weight gain; Related to Chronic Data: death

TDLo (Oral-Mouse) 181 g/kg/72 weeks-continuous: Tumorigenic: carcinogenic by RTECS criteria; Lungs, Thorax, or Respiration: tumors; Blood: lymphoma, including Hodgkin's disease

TDLo (Intraperitoneal-Rat) 1750 mg/kg: female 7 day(s) pre-mating: Reproductive: Fertility: post-implantation mortality (e.g. dead and/or resorbed implants per total number of implants)

TDLo (Intraperitoneal-Mouse) 60 mg/kg: female 8-14 day(s) after conception: Reproductive: Effects on Fetus: fetal death; Specific Developmental Abnormalities: other developmental abnormalities

TDLo (Unreported) 750 mg/kg: female 30 day(s) pre-mating: Reproductive: Maternal Effects: uterus, cervix, vagina

TD (Oral-Rat) 27 g/kg/35 weeks-continuous: Tumorigenic: equivocal tumorigenic agent by RTECS criteria; Skin and Appendages: tumors; Reproductive: Tumorigenic effects: uterine tumors

TD (Oral-Rat) 3 g/kg/14 weeks-continuous: Tumorigenic: neoplastic by RTECS criteria; Skin and Appendages: tumors

TD (Oral-Mouse) 8 g/kg/14 weeks-continuous: Tumorigenic: neoplastic by RTECS criteria; Lungs, Thorax, or Respiration: tumors; Blood: lymphoma, including Hodgkin's disease

TD (Oral-Mouse) 21,800 mg/kg/2 years-intermittent: Tumorigenic: carcinogenic by RTECS criteria; Liver: tumors

TD (Oral-Mouse) 1680 mg/kg: Tumorigenic: carcinogenic by RTECS criteria; Reproductive: trans-placental tumorigenesis; Lungs, Thorax, or Respiration: tumors

Cytogenetic Analysis (Unreported-Human) 86 mg/kg/30 days

Cytogenetic Analysis (Human-Lymphocyte) 500 mg/L

Cytogenetic Analysis (Oral-Human) 250 mg/kg/10 days-continuous

DNA Damage (Oral-Human) 214.3 mg/kg/10 days

DNA Damage (Human-Lymphocyte) 10 mg/L/30 minutes

Body Fluid Assay (Human Bacteria-Salmonella typhimurium) 10 mg/kg

Mutation in Microorganisms (Bacteria-Salmonella typhimurium) 25 µg/plate

Mutation in Microorganisms (Bacteria-Salmonella typhimurium) 50 µg/plate

Mutation in Microorganisms (Bacteria-Escherichia coli) 100 µmol/L

METRONIDAZOLE (continued):

Mutation in Microorganisms (Bacteria-Escherichia coli) 1 g/L

Mutation in Microorganisms (Bacteria-Klebsiella pneumoniae) 20 µmol/L/20 hours

Mutation in Microorganisms (Bacteria-Salmonella typhimurium) 156 µg/plate/20 minutes

Mutation in Microorganisms (Bacteria-Salmonella typhimurium) 156 µg/plate/20 minutes

Mutation in Microorganisms (Mold-Neurospora crassa) 8800 mg/L

Mutation in Microorganisms (Microorganism-Not Otherwise Specified) 25 µmol/L

Mutation Test Systems-Not Otherwise Specified (Bacteria-Escherichia coli) 4 mg/L

Mutation Test Systems-Not Otherwise Specified (Microorganism-Not Otherwise Specified) 5 mg/L

DNA Repair (Bacteria-Escherichia coli) 200 µg/disc

DNA Repair (Bacteria-Bacillus subtilis) 200 µg/disc

DNA Adduct (Bacteria-Escherichia coli) 2 µmol

DNA Adduct (Mammal-Species Unspecified Lymphocyte) 60 µmol/L

Phage Inhibition Capacity (Bacteria-Escherichia coli) 500 µg/plate

DNA Inhibition (Microorganism-Not Otherwise Specified) 1 mg/L

DNA Inhibition (Microorganism-Not Otherwise Specified) 5 mg/L

DNA Inhibition (Mouse-Lymphocyte) 30 mmol/L/1 hour-continuous

DNA Inhibition (Mouse Cells-Not Otherwise Specified) 100 mg/L

DNA Inhibition (Hamster-Lung) 1 mmol/L/6 days-continuous

DNA Damage (Rat-Liver) 3 mmol/L

DNA Damage (Mouse-Lymphocyte) 30 mmol/L/4 hours-continuous

DNA Damage (Mouse-Fibroblast) 300 µmol/L

Body Fluid Assay (Rat Bacteria-Salmonella typhimurium) 800 mg/kg

Body Fluid Assay (Rat Bacteria-Salmonella typhimurium) 100 mg/kg

Cytogenetic Analysis (Oral-Mouse) 1200 mg/kg

Cytogenetic Analysis (Hamster-Lung) 10 mmol/L

Sister Chromatid Exchange (Oral-Hamster) 125 mg/kg

Host-Mediated Assay (Mouse Bacteria-Salmonella typhimurium) 400 mg/kg/5 days

Host-Mediated Assay (Mouse Bacteria-Escherichia coli) 4 mg/kg/2 hours

Host-Mediated Assay (Mouse Yeast-Saccharomyces cerevisiae) 25 mmol/kg

Host-Mediated Assay (Hamster-Embryo) 200 mg/kg

CARCINOGENIC INFORMATION: Metronidazole has shown evidence of carcinogenic activity in a number of studies involving chronic, oral administration in mice and rats but not in studies involving hamsters.

The remaining components of this product are not found on the following lists: U.S. EPA, U.S. NTP, U.S. OSHA, U.S. NIOSH, GERMAN MAK, IARC, or ACGIH and therefore are neither considered to be nor suspected to be cancer-causing agents by these agencies.

REPRODUCTIVE TOXICITY INFORMATION: The active component of this product, Metronidazole is rated as Pregnancy Category B (NO EVIDENCE OF RISK, Human evidence is negative, but animal evidence is positive. Alternately, there is no human evidence and animal evidence is negative). Listed below is information concerning the effects of this compound on animal or human reproductive system.

Mutagenicity: Metronidazole has shown evidence of mutagenic activity in several in vitro bacterial assay systems. In addition, a dose-response increase in the frequency of micronuclei was observed in mice after intraperitoneal injections and an increase in chromosomal aberrations have been reported in patients with Crohn's disease who were treated with 200-1200 mg/day of Metronidazole for 1 to 24 months; however, no excess chromosomal aberrations in circulating human lymphocytes have been observed in patients treated for 8 months.

Embryotoxicity/Teratogenicity: The components of this product are not reported to cause human embryotoxic or teratogenic effects.

Reproductive Toxicity: Metronidazole crosses the placental barrier and enters the fetal circulation rapidly. No fetotoxicity was observed after oral Metronidazole in rats or mice.

ACGIH BIOLOGICAL EXPOSURE INDICES (BEIs): Currently, ACGIH Biological Exposure Indices (BEIs) have not been determined for the components of this product.

12. ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

MOBILITY: This product has not been tested for soil absorption or mobility. The following information is available for the components of this product:

BENZYL ALCOHOL:

Experimental Koc values for Benzyl Alcohol are < 5 for three different soils; Apison (0.11% organic carbon), Fullerton (0.06% organic carbon), and Dormont (1.2% organic carbon). An experimental Koc of 15 was determined for Benzyl Alcohol on a red-brown Australian soil (1.09% organic carbon). According to a classification scheme, these Koc values suggest that Benzyl Alcohol is expected to have very high mobility in soil.

GLYCERIN:

Based on an experimental log octanol/water partition coefficient of -1.76 and its water solubility, 1,220,000 mg/L at 5°C, soil adsorption coefficients for Glycerin can be estimated at 3 and 2, respectively, using regression-derived equations. The magnitude of these values indicate that glycerin will display very high mobility in soil.

ISOPROPYL PALMITATE:

Using a structure estimation method based on molecular connectivity indices, the K_{oc} for Isopropyl Palmitate can be estimated to be about 52,000. According to a classification scheme, this estimated K_{oc} value suggests that Isopropyl Palmitate is expected to be immobile in soil.

SORBITOL:

The Koc of Sorbitol is estimated as approximately 2, using a log Kow of -2.2 and a regression-derived equation. According to a classification scheme, this estimated Koc value suggests that Sorbitol is expected to have very high mobility in soil.

PERSISTENCE AND BIODEGRADABILITY: This product has not been tested for persistence or biodegradability. The following information is available for the components of this product:

BENZYL ALCOHOL:

Persistence and Biodegradability: If released to air, a vapor pressure of 0.094 mm Hg at 25°C indicates Benzyl Alcohol will exist solely as a vapor in the ambient atmosphere. Vapor-phase Benzyl Alcohol will be degraded in the atmosphere by reaction with photochemically-produced hydroxyl radicals; the half-life for this reaction in air is estimated to be 17 hours. If released to soil, Benzyl Alcohol is expected to have very high mobility based upon Koc values of less than 5 to 15 measured in various soils. Volatilization from moist soil surfaces is not expected to be an important fate process based upon an estimated Henry's Law constant of 3.1X10⁻⁷ atm-cu m/mole. Benzyl Alcohol is not expected to volatilize rapidly from dry soil surfaces based on its vapor pressure. Benzyl Alcohol is expected to undergo biodegradation under both aerobic and anaerobic conditions based upon results in a number of aqueous biodegradation tests. If released into water, Benzyl Alcohol is not expected to adsorb to suspended solids and sediment based upon the Koc data. Volatilization from water surfaces is not expected to be an important fate process based upon this compound's estimated Henry's Law constant. Estimated volatilization half-lives for a model river and model lake are 75 days and 2.2 years, respectively. An estimated BCF of 1 suggests the potential for bioconcentration in aquatic organisms is low. Hydrolysis is not expected to be an important environmental fate process since Benzyl Alcohol lacks hydrolyzable functional groups.

GLYCERIN:

Persistence and Biodegradability: If released to soil, glycerin is expected to undergo rapid biodegradation under aerobic conditions. It is expected to display very high mobility in soil and it is not expected to significantly volatilize to the atmosphere. If released to water, glycerin is expected to rapidly degrade under aerobic conditions. Biodegradation in seawater and under anaerobic conditions is also expected. Glycerin is not expected to bioconcentrate in fish and aquatic organisms nor is it expected to adsorb to sediment and suspended organic matter. Volatilization to the atmosphere is expected to be slower than for water itself. If released to the atmosphere, Glycerin may undergo a gas-phase oxidation with photochemically produced hydroxyl radicals with a half-life of 33 hrs. It may also undergo atmospheric removal by wet deposition processes.

ISOPROPYL PALMITATE:

If released to air, an estimated vapor pressure of 5.6X10⁻⁵ mm Hg at 25°C indicates Isopropyl Palmitate will exist in both the vapor and particulate phases in the ambient atmosphere. Vapor-phase Isopropyl Palmitate will be degraded in the atmosphere by reaction with photochemically-produced hydroxyl radicals; the half-life for this reaction in air is estimated to be 17 hours. Particulate-phase Isopropyl Palmitate will be removed from the atmosphere by wet and dry deposition. If released to soil, Isopropyl Palmitate is expected to have no mobility based upon an estimated K_{oc} of 52,000. Volatilization from moist soil surfaces is expected to be an important fate process based upon an estimated Henry's Law constant of 0.016 atm-cu m/mole. However, adsorption to soil is expected to attenuate volatilization. Isopropyl Palmitate is expected to rapidly biodegrade in aerobic soils as suggested by the rapid biodegradation of structurally similar long-chain fatty acid esters. If released into water, Isopropyl Palmitate is expected to adsorb to suspended solids and sediment in the water column based upon the estimated Koc. Isopropyl Palmitate is expected to rapidly biodegrade in aerobic waters as suggested by the rapid biodegradation of structurally similar long-chain fatty acid esters. Volatilization from water surfaces is expected to be an important fate process based upon this compound's estimated Henry's Law constant. Estimated volatilization half-lives for a model river and model lake are 5 hours and 7 days, respectively. However, volatilization from water surfaces is expected to be attenuated by adsorption to suspended solids and sediment in the water column. The volatilization half-life from a model pond is estimated to be about 61 hours ignoring adsorption; when considering maximum adsorption the volatilization half-life increases to 15 months. An estimated base-catalyzed second-order hydrolysis rate constant of 0.021 L/mole-sec corresponds to half-lives of 10 and 1 years at pH values of 7 and 8, respectively.

SORBITOL:

If released to air, an estimated vapor pressure of 4.9X10⁻⁹ mm Hg at 25°C indicates Sorbitol will exist in the particulate phase. Particulate-phase Sorbitol will be removed from the atmosphere by wet and dry deposition. If released to soil, Sorbitol is expected to have very high mobility based upon an estimated Koc of 2. Volatilization from moist soil surfaces is not expected to be an important fate process based upon an estimated Henry's Law constant of 7.3X10⁻¹³ atm-cu m/mole. Sorbitol is a simple sugar alcohol and should be readily biodegraded in the environment. If released into water, Sorbitol is not expected to adsorb to suspended solids and sediment in the water column based upon the estimated Koc. Volatilization from water surfaces is not expected to be an important fate process based upon this compound's estimated Henry's Law constant.

BIOACCUMULATION: This product has not been tested for bioconcentration. The following information is available for the components of this product:

BENZYL ALCOHOL:

An estimated BCF of 1 was calculated for Benzyl Alcohol, using a log Kow of 1.1 and a regression-derived equation. According to a classification scheme, this BCF suggests the potential for bioconcentration in aquatic organisms is low.

GLYCERIN:

Based on an experimental log octanol/water partition coefficient of -1.76 and its water solubility, 1,220,000 mg/L at 5°C, bioconcentration factors for Glycerin can be estimated at 3 and 0.2, respectively, using regression-derived equations. The magnitude of these values indicate that bioconcentration of Glycerin in fish and aquatic organisms will not be significant. Log K_{ow} = -1.76.

ISOPROPYL PALMITATE:

An estimated BCF of 53 was calculated for Isopropyl Palmitate using an estimated log K_{ow} of 8.16 and a regression-derived equation. According to a classification scheme, the estimated BCF suggests the potential for bioconcentration in aquatic organisms is moderate.

SORBITOL:

An estimated BCF of 1 was calculated for Sorbitol, using a log Kow of -2.2 and a regression-derived equation. According to a classification scheme, this BCF suggests the potential for bioconcentration in aquatic organisms is low.

ECOTOXICITY: No specific information is currently available on the effect of this product on plants or animals in the environment. This product may be harmful to contaminated terrestrial and aquatic plant and animal life, especially in large quantities. The following are aquatic toxicity data currently available for components of this product.

BENZYL ALCOHOL:

LC₅₀ (*Scenedesmus quadricauda*) 96 hours = 640 ppm
 LC₅₀ (*Lepomis macrochirus* bluegill sunfish) 24 hours = >5 mg/L
 LC₅₀ (*Leuciscus idus*) 48 hours = 630 mg/L
 LC₅₀ (*Salmo trutta*) 24 hours = >5 mg/L
 LC₅₀ (*Carassius auratus*) 24 hours = > 5 mg/L
 LC₅₀ (*Daphnia*) 48 hours = 369 ppm
 LC₅₀ (*Pimephales promelas* fathead minnows) 24 hours = 770 mg/L
 LC₅₀ (*Pimephales promelas* fathead minnows) 48 hours = 770 mg/L (static bioassay in Lake Superior water at 18-22°C)
 LC₅₀ (*Pimephales promelas* fathead minnows) 72 hours = 480 mg/L (static bioassay in Lake Superior water at 18-22°C)
 LC₅₀ (*Pimephales promelas* fathead minnows) 96 hours = 460 mg/L (static bioassay in Lake Superior water at 18-22°C)

BENZYL ALCOHOL (continued):

LC₅₀ (*Lepomis macrochirus* bluegill sunfish) 96 hours = 10 ppm/L (static bioassay in fresh water at 23°C, mild aeration after 24 hours)
 LC₅₀ (*Medina beryllina* tidewater silverside fish) 96 hours = 15 ppm (static bioassay in synthetic seawater at 23°C, mild aeration after 24 hours)
 LC₅₀S (*Lepomis macrochirus* bluegill sunfish) 96 hours = 10 mg/L
 LC₅₀ S (*Medina beryllina* tidewater silverside fish) 96 hours = 15 mg/L
 LC₅₀ (*Daphnia*) 24 hours = 55; 400 mg/L
 LC₅₀ (*Petromyzon marinus* larvae) 24 hours = >5 mg/L
 LC₁₀₀ (*Daphnia*) 24 hours = 100 mg/L
 EC₀ (*Daphnia*) 24 hours = 26; 300 mg/L
 EC₀ (*Anabaena inaequalis*) 3 hours = 30 mg/L
 EC₀ (*E. coli*) 48 hours = 1,000 mg/L
 EC₁₀ (*Pseudomonas putida*) 16 hours = 658 mg/L
 EC₅₀ (*Photobacterium phosphoreum*) 30 minutes = 71 mg/L

12. ECOLOGICAL INFORMATION (Continued)

ECOTOXICITY (continued):

BENZYL ALCOHOL (continued):

EC₅₀ (*Photobacterium phosphoreum*) 5 minutes = 50 mg/L
 EC₅₀ (*Scenedesmus quadricauda*) 3 hours = 79 mg/L
 EC₅₀ (*Haematococcus pluvialis*) 4 hours = 2,600 mg/L
 EC₅₀ (*Anabaena cylindrica*) 3 hours = 90 mg/L
 EC₅₀ (*Anabaena variabilis*) 3 hours = 35 mg/L

BENZYL ALCOHOL (continued):

EC₅₀ (*Chlorella pyrenoidosa*) 3 hours = 95 mg/L
GLYCERIN:
 EC₀ (*Pseudomonas putida* bacteria) 16 hours = >10,000 mg/L
 EC₀ (*Microcystis aeruginosa* algae) 8 days = 2,900 mg/L

GLYCERIN:

EC₀ (*Scenedesmus quadricauda* green algae) 7 days = > 10,000 mg/L
 EC₀ (*Entosiphon sulcatum* protozoa) 72 hours = 3,200 mg/L
 EC₀ (*Uronema parduczi* Chatton-Lwoff protozoa) = > 10,000 mg/L
 LC₅₀ (goldfish) 24 hours = > 5,000 mg/L

ENVIRONMENTAL EXPOSURE CONTROLS: Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways.

OTHER ADVERSE EFFECTS: No component of this product is known to have ozone depletion potential.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS: It is the responsibility of the generator to determine at the time of disposal whether the product meets the criteria of a hazardous waste per regulations of the area in which the waste is generated and/or disposed of. Waste disposal must be in accordance with appropriate Federal, State, and local regulations. This product, if unaltered by use, may be disposed of by treatment at a permitted facility or as advised by your local hazardous waste regulatory authority. Shipment of wastes must be done with appropriately permitted and registered transporters.

DISPOSAL CONTAINERS: Waste materials must be placed in and shipped in appropriate 5-gallon or 55-gallon poly or metal waste pails or drums. Permeable cardboard containers are not appropriate and should not be used. Ensure that any required marking or labeling of the containers be done to all applicable regulations.

PRECAUTIONS TO BE FOLLOWED DURING WASTE HANDLING: Wear proper protective equipment when handling waste materials.

PREPARING WASTES FOR DISPOSAL: Waste disposal must be in accordance with appropriate U.S. Federal, State, and local regulations or with regulations of Canada. This product, if unaltered by handling, may be disposed of by treatment at a permitted facility or as advised by your local hazardous waste regulatory authority. All gowns, gloves, and disposable materials used in the preparation or handling of this drug should be disposed of in accordance with established hazardous waste disposal procedures. Handle as if capable of transmitting infectious agents. Incineration is recommended. Reusable equipment should be cleaned with soap and water.

U.S. EPA WASTE NUMBER: Not applicable to wastes consisting only of this product.

14. TRANSPORTATION INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION SHIPPING REGULATIONS: This product is not classified as hazardous under regulations of U.S. DOT 49 CFR 172.101.

TRANSPORT CANADA TRANSPORTATION OF DANGEROUS GOODS REGULATIONS: This product is not classified as Dangerous Goods, per regulations of Transport Canada.

15. REGULATORY INFORMATION

UNITED STATES REGULATIONS:

U.S. SARA REPORTING REQUIREMENTS: The components of this product are not subject to the reporting requirements of Sections 302, 304, and 313 of Title III of the Superfund Amendments and Reauthorization Act.

U.S. SARA THRESHOLD PLANNING QUANTITY: There are no specific Threshold Planning Quantities for any component of this product. The default Federal MSDS submission and inventory requirement filing threshold of 10,000 lb (4,540 kg) therefore applies, per 40 CFR 370.20.

U.S. CERCLA REPORTABLE QUANTITIES (RQ): Not applicable.

U.S. TSCA INVENTORY STATUS: This product is regulated by the Food and Drug Administration; it is not subject to requirements under TSCA.

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65): Metronidazole, the active component of this product is on the Proposition 65 list. WARNING! This product contains a chemical known to the State of California to cause cancer.

OTHER U.S. FEDERAL REGULATIONS: Not applicable.

CANADIAN REGULATIONS:

CANADIAN DSL/NDL INVENTORY STATUS: This product regulated by the Therapeutic Products Programme (TPP) of Health Canada and so it is exempt from requirements of the DSL/NDL Inventory.

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS: The components of this product are not on the CEPA Priorities Substances Lists.

CANADIAN WHMIS CLASSIFICATION AND SYMBOLS: The WHMIS Requirements of the Hazardous Products Act does not apply in respect of the advertising, sale or importation of any cosmetic, device, drug or food within the meaning of the Food and Drugs Act.

16. OTHER INFORMATION

ANSI LABELING (Based on 129.1, Provided to Summarize Occupational Exposure Hazards): CAUTION! CONTAINS A SUSPECT CANCER HAZARD. Cancer hazard depends on duration and concentration of exposure. MAY CAUSE ALLERGIC REACTION. MAY CAUSE SKIN AND EYE IRRITATION. Avoid contact with skin, eyes, and clothing. Wash thoroughly after handling. Wear gloves, goggles, and appropriate body protection during handling or administration. FIRST-AID: In case of contact, flush skin or eyes with plenty of water. If adverse respiratory reaction occurs from allergic reaction, give oxygen and seek immediate medical attention. If ingested, DO NOT induce vomiting—seek immediate medical attention. IN CASE OF FIRE: Use water fog, dry chemical, CO₂, or “alcohol” foam. IN CASE OF SPILL: Wipe up spilled product. Place residual in appropriate container and seal. Dispose of according to applicable regulations. Consult Material Safety Data Sheet for additional information.

This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Fougera's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this product is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

PREPARED BY: CHEMICAL SAFETY ASSOCIATES, Inc. • PO Box 1961, Hilo, HI 96721 • 800/441-3365 • 808/969-4846
DATE OF PRINTING: February 1, 2012

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these, which are commonly used, include the following:

CAS #: This is the Chemical Abstract Service Number that uniquely identifies each constituent.

EXPOSURE LIMITS IN AIR:

CEILING LEVEL: The concentration that shall not be exceeded during any part of the working exposure.

DFG MAKs: Federal Republic of Germany Maximum Concentration Values in the workplace. Exposure limits are given as TWA (Time-Weighted Average) or PEAK (short-term exposure) values.

DFG MAK Germ Cell Mutagen Categories: **1:** Germ cell mutagens that have been shown to increase the mutant frequency in the progeny of exposed humans. **2:** Germ cell mutagens that have been shown to increase the mutant frequency in the progeny of exposed mammals. **3A:** Substances that have been shown to induce genetic damage in germ cells of human of animals, or which produce mutagenic effects in somatic cells of mammals *in vivo* and have been shown to reach the germ cells in an active form. **3B:** Substances that are suspected of being germ cell mutagens because of their genotoxic effects in mammalian somatic cell *in vivo*; in exceptional cases, substances for which there are no *in vivo* data, but that are clearly mutagenic *in vitro* and structurally related to known *in vivo* mutagens. **4:** Not applicable (Category 4 carcinogenic substances are those with non-genotoxic mechanisms of action. By definition, germ cell mutagens are genotoxic. Therefore, a Category 4 for germ cell mutagens cannot apply. At some time in the future, it is conceivable that a Category 4 could be established for genotoxic substances with primary targets other than DNA [e.g. purely aneugenic substances] if research results make this seem sensible.) **5:** Germ cell mutagens, the potency of which is considered to be so low that, provided the MAK value is observed, their contribution to genetic risk for humans is expected not to be significant.

DFG MAK Pregnancy Risk Group Classification: **Group A:** A risk of damage to the developing embryo or fetus has been unequivocally demonstrated. Exposure of pregnant women can lead to damage of the developing organism, even when MAK and BAT (Biological Tolerance Value for Working Materials) values are observed. **Group B:** Currently available information indicates a risk of damage to the developing embryo or fetus must be considered to be probable. Damage to the developing organism cannot be excluded when pregnant women are exposed, even when MAK and BAT values are observed. **Group C:** There is no reason to fear a risk of damage to the developing embryo or fetus when MAK and BAT values are observed. **Group D:** Classification in one of the groups A–C is not yet possible because, although the data available may indicate a trend, they are not sufficient for final evaluation.

IDLH: Immediately Dangerous to Life and Health. This level represents a concentration from which one can escape within 30-minutes without suffering escape-preventing or permanent injury.

LQ: Limit of Quantitation.

NE: Not Established. When no exposure guidelines are established, an entry of NE is made for reference.

NIC: Notice of Intended Change.

NIOSH CEILING: The exposure that shall not be exceeded during any part of the workday. If instantaneous monitoring is not feasible, the ceiling shall be assumed as a 15-minute TWA exposure (unless otherwise specified) that shall not be exceeded at any time during a workday.

NIOSH RELs: NIOSH's Recommended Exposure Limits.

PEL: OSHA's Permissible Exposure Limits. This exposure value means exactly the same as a TLV, except that it is enforceable by OSHA. The OSHA Permissible Exposure Limits are based in the 1989 PELs and the June, 1993 Air Contaminants Rule (Federal Register: 58: 35338-35351 and 58: 40191). Both the current PELs and the vacated PELs are indicated. The phrase, “Vacated 1989 PEL” is placed next to the PEL that was vacated by Court Order.

SKIN: Used when there is a danger of cutaneous absorption.

STEL: Short Term Exposure Limit, usually a 15-minute time-weighted average (TWA) exposure that should not be exceeded at any time during a workday, even if the 8-hr TWA is within the TLV-TWA, PEL-TWA or REL-TWA.

TLV: Threshold Limit Value. An airborne concentration of a substance that represents conditions under which it is generally believed that nearly all workers may be repeatedly exposed without adverse effect. The duration must be considered, including the 8-hour.

TWA: Time Weighted Average exposure concentration for a conventional 8-hr (TLV, PEL) or up to a 10-hr (REL) workday and a 40-hr workweek.

WEEL: Workplace Environmental Exposure Limits from the AIHA.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM HAZARD RATINGS:

This rating system was developed by the National Paint and Coatings Association and has been adopted by industry to identify the degree of chemical hazards.

HEALTH HAZARD: 0 Minimal Hazard: No significant health risk, irritation of skin or eyes not anticipated. *Skin Irritation:* Essentially non-irritating. Mechanical irritation may occur. *PII or Draize = 0. Eye Irritation:* Essentially non-irritating, minimal effects clearing in < 24 hours. Mechanical irritation may occur. *Draize = 0. Oral Toxicity LD₅₀ Rat > 5000 mg/kg. Dermal Toxicity LD₅₀ Rat or Rabbit > 2000 mg/kg. Inhalation Toxicity 4-hrs LC₅₀ Rat > 20 mg/L. 1 Slight Hazard:* Minor reversible injury may occur; may irritate the stomach if swallowed; may defat the skin and exacerbate existing dermatitis. *Skin Irritation:* Slightly or mildly irritating. *PII or Draize > 0 < 5. Eye Irritation:* Slightly to mildly irritating, but reversible within 7 days. *Draize > 5 25. Oral Toxicity LD₅₀ Rat > 500–5000 mg/kg. Dermal Toxicity LD₅₀ Rat or Rabbit > 1000–2000 mg/kg. Inhalation Toxicity LC₅₀ 4-hrs Rat > 2–200 mg/L. 2 Moderate Hazard:* Temporary or transitory injury may occur; prolonged exposure may affect the CNS. *Skin Irritation:* Moderately irritating; primary irritant; sensitizer. *PII or Draize ≥ 5, with no destruction of dermal tissue. Eye Irritation:* Moderately to severely irritating; reversible corneal opacity; corneal involvement or irritation clearing in 8–21 days. *Draize = 26–100, with reversible effects. Oral Toxicity LD₅₀ Rat > 50–500 mg/kg. Dermal Toxicity LD₅₀ Rat or Rabbit > 200–1000 mg/kg. Inhalation Toxicity LC₅₀ 4-hrs Rat > 0.5–2 mg/L. 3 Serious Hazard:* Major injury likely unless prompt action is taken and medical treatment is given; high level of toxicity; corrosive. *Skin Irritation:* Severely irritating and/or corrosive; may cause destruction of dermal tissue, skin burns, and dermal necrosis. *PII or Draize > 5–8, with destruction of tissue. Eye Irritation:* Corrosive, irreversible destruction of ocular tissue; corneal involvement or irritation persisting for more than 21 days. *Draize > 80 with effects irreversible in 21 days. Oral Toxicity LD₅₀ Rat > 1–50 mg/kg. Dermal Toxicity LD₅₀ Rat or Rabbit > 20–200 mg/kg. Inhalation Toxicity LC₅₀ 4-hrs Rat > 0.05–0.5 mg/L. 4 Severe Hazard:* Life-threatening; major or permanent damage may result from single or repeated exposures; extremely toxic; irreversible injury may result from brief contact. *Skin Irritation:* Not appropriate. Do not rate as a 4, based on skin irritation alone. *Eye Irritation:* Not appropriate. Do not rate as a 4, based on eye irritation alone. *Oral Toxicity LD₅₀ Rat ≤ 1 mg/kg. Dermal Toxicity LD₅₀ Rat or Rabbit ≤ 20 mg/kg. Inhalation Toxicity LC₅₀ 4-hrs Rat ≤ 0.05 mg/L.*

FLAMMABILITY HAZARD: 0 Minimal Hazard: Materials that will not burn in air when exposed to a temperature of 815.5°C (1500°F) for a period of 5 minutes. **1 Slight Hazard:** Materials that must be pre-heated before ignition can occur. Material requires considerable pre-heating, under all ambient temperature conditions before ignition and combustion can occur. This usually includes the following: Materials that will burn in air when exposed to a temperature of 815.5°C (1500°F) for a period of 5 minutes or less; Liquids, solids and semisolids having a flash point at or above 93.3°C (200°F) (i.e. OSHA Class IIIB); and Most ordinary combustible materials (e.g. wood, paper, etc.). **2 Moderate Hazard:** Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur. Materials in this degree would not, under normal conditions, form hazardous atmospheres in air, but under high ambient temperatures or moderate heating may release vapor in sufficient quantities to produce hazardous atmospheres with air. This usually includes the following: Liquids having a flash-point at or above 37.8°C (100°F); Solid materials in the form of coarse dusts that may burn rapidly but that generally do not form explosive atmospheres; Solid materials in a fibrous or shredded form that may burn rapidly and create flash fire hazards (e.g. cotton, sisal, hemp); and Solids and semisolids (e.g. viscous and slow flowing as asphalt) that readily give off flammable vapors. **3 Serious Hazard:** Liquids and solids that can be ignited under almost all ambient temperature conditions. Materials in this degree produce hazardous atmospheres with air under almost all ambient temperatures, or, unaffected by ambient temperature, are readily ignited under almost all conditions. This usually includes the following: Liquids having a flash point below 22.8°C (73°F) and having a boiling point at or above 38°C (100°F) and those liquids having a flash point at or above 22.8°C (73°F) and below 37.8°C (100°F) (i.e. OSHA Class IB and IC); Materials that on account of their physical form or environmental conditions can form explosive mixtures with air and are readily dispersed in air (e.g., dusts of combustible solids, mists or droplets of flammable liquids); and Materials that burn extremely rapidly, usually by reason of self-contained oxygen (e.g. dry nitrocellulose and many organic peroxides). **4 Severe Hazard:** Materials that will rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air, and that will burn readily.

DEFINITION OF TERMS (Continued)

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM HAZARD RATINGS (continued):

FLAMMABILITY HAZARD (continued): 4 (continued): This usually includes the following: Flammable gases; Flammable cryogenic materials; Any liquid or gaseous material that is liquid while under pressure and has a flash point below 22.8°C (73°F) and a boiling point below 37.8°C (100°F) (i.e. OSHA Class IA); and Materials that ignite spontaneously when exposed to air at a temperature of 54.4°C (130°F) or below (pyrophoric).

PHYSICAL HAZARD: 0 Water Reactivity: Materials that do not react with water. *Organic Peroxides:* Materials that are normally stable, even under fire conditions and will not react with water. *Explosives:* Substances that are Non-Explosive. *Compressed Gases:* No Rating. *Pyrophorics:* No Rating. *Oxidizers:* No 0 rating. *Unstable Reactives:* Substances that will not polymerize, decompose, condense, or self-react. 1 *Water Reactivity:* Materials that change or decompose upon exposure to moisture. *Organic Peroxides:* Materials that are normally stable, but can become unstable at high temperatures and pressures. These materials may react with water, but will not release energy violently. *Explosives:* Division 1.5 & 1.6 explosives. Substances that are very insensitive explosives or that do not have a mass explosion hazard. *Compressed Gases:* Pressure below OSHA definition. *Pyrophorics:* No Rating. *Oxidizers:* Packaging Group III oxidizers; Solids: any material that in either concentration tested, exhibits a mean burning time less than or equal to the mean burning time of a 3:7 potassium bromate/cellulose mixture and the criteria for Packing Group I and II are not met. Liquids: any material that exhibits a mean pressure rise time less than or equal to the pressure rise time of a 1:1 nitric acid (65%)/cellulose mixture and the criteria for Packing Group I and II are not met. *Unstable Reactives:* Substances that may decompose, condense, or self-react, but only under conditions of high temperature and/or pressure and have little or no potential to cause significant heat generation or explosion hazard. Substances that readily undergo hazardous polymerization in the absence of inhibitors. 2 *Water Reactivity:* Materials that may react violently with water. *Organic Peroxides:* Materials that, in themselves, are normally unstable and will readily undergo violent chemical change, but will not detonate. These materials may also react violently with water. *Explosives:* Division 1.4 explosives. Explosive substances where the explosive effects are largely confined to the package and no projection of fragments of appreciable size or range are expected. An external fire must not cause virtually instantaneous explosion of almost the entire contents of the package. *Compressed Gases:* Pressurized and meet OSHA definition but < 514.7 psi absolute at 21.1°C (70°F) [500 psig]. *Pyrophorics:* No Rating. *Oxidizers:* Packing Group II oxidizers. Solids: any material that, in either concentration tested, exhibits a mean burning time less than or equal to the mean burning time of a 2:3 potassium bromate/cellulose mixture and the criteria for Packing Group I are not met. Liquids: any material that exhibits a mean pressure rise time less than or equal to the pressure rise of a 1:1 aqueous sodium chlorate solution (40%)/cellulose mixture and the criteria for Packing Group I are not met. *Reactive:* Substances that may polymerize, decompose, condense, or self-react at ambient temperature and/or pressure, but have a low potential (or low risk) for significant heat generation or explosion. Substances that readily form peroxides upon exposure to air or oxygen at room temperature. 3 *Water Reactivity:* Materials that may form explosive reactions with water. *Organic Peroxides:* Materials that are capable of detonation or explosive reaction, but require a strong initiating source or must be heated under confinement before initiation; or materials that react explosively with water. *Explosives:* Division 1.3 explosives. Explosive substances that have a fire hazard and either a minor blast hazard or a minor projection hazard or both, but do not have a mass explosion hazard. *Compressed Gases:* Pressure ≥ 514.7 psi absolute at 21.1°C (70°F) [500 psig]. *Pyrophorics:* No Rating. *Oxidizers:* Packing Group I oxidizers. Solids: any material that, in either concentration tested, exhibits a mean burning time less than the mean burning time of a 3:2 potassium bromate/cellulose mixture. Liquids: any material that spontaneously ignites when mixed with cellulose in a 1:1 ratio, or which exhibits a mean pressure rise time less than the pressure rise time of a 1:1 perchloric acid (50%)/cellulose mixture. *Unstable Reactives:* Substances that may polymerize, decompose, condense, or self-react at ambient temperature and/or pressure and have a moderate potential (or moderate risk) to cause significant heat generation or explosion. 4 *Water Reactivity:* Materials that react explosively with water without requiring heat or confinement. *Organic Peroxides:* Materials that are readily capable of detonation or explosive decomposition at normal temperature and pressures. *Explosives:* Division 1.1 & 1.2 explosives. Explosive substances that have a mass explosion hazard or have a projection hazard. A mass explosion is one that affects almost the entire load instantaneously. *Compressed Gases:* No Rating. *Pyrophorics:* Add to the definition of Flammability 4. *Oxidizers:* No 4 rating. *Unstable Reactives:* Substances that may polymerize, decompose, condense, or self-react at ambient temperature and/or pressure and have a high potential (or high risk) to cause significant heat generation or explosion.

NATIONAL FIRE PROTECTION ASSOCIATION HAZARD RATINGS:

HEALTH HAZARD: 0 Materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials. Gases and vapors with an LC₅₀ for acute inhalation toxicity greater than 10,000 ppm. Dusts and mists with an LC₅₀ for acute inhalation toxicity greater than 200 mg/L. Materials with an LD₅₀ for acute dermal toxicity greater than 2000 mg/kg. Materials with an LD₅₀ for acute oral toxicity greater than 2000 mg/kg. Materials essentially non-irritating to the respiratory tract, eyes, and skin. 1 Materials that, under emergency conditions, can cause significant irritation. Gases and vapors with an LC₅₀ for acute inhalation toxicity greater than 5,000 ppm but less than or equal to 10,000 ppm. Dusts and mists with an LC₅₀ for acute inhalation toxicity greater than 10 mg/L but less than or equal to 200 mg/L. Materials with an LD₅₀ for acute dermal toxicity greater than 1000 mg/kg but less than or equal to 2000 mg/kg. Materials that slightly to moderately irritate the respiratory tract, eyes and skin. Materials with an LD₅₀ for acute oral toxicity greater than 500 mg/kg but less than or equal to 2000 mg/kg. 2 Materials that, under emergency conditions, can cause temporary incapacitation or residual injury. Gases with an LC₅₀ for acute inhalation toxicity greater than 3,000 ppm but less than or equal to 5,000 ppm. Any liquid whose saturated vapor concentration at 20°C (68°F) is equal to or greater than one-fifth its LC₅₀ for acute inhalation toxicity, if its LC₅₀ is less than or equal to 5000 ppm and that does not meet the criteria for either degree of hazard 3 or degree of hazard 4. Dusts and mists with an LC₅₀ for acute inhalation toxicity greater than 2 mg/L but less than or equal to 10 mg/L.

NATIONAL FIRE PROTECTION ASSOCIATION HAZARD RATINGS (continued):

HEALTH HAZARD (continued): 2 (continued): Materials with an LD₅₀ for acute dermal toxicity greater than 200 mg/kg but less than or equal to 1000 mg/kg. Compressed liquefied gases with boiling points between -30°C (-22°F) and -55°C (-66.5°F) that cause severe tissue damage, depending on duration of exposure. Materials that are respiratory irritants. Materials that cause severe, but reversible irritation to the eyes or are lachrymators. Materials that are primary skin irritants or sensitizers. Materials whose LD₅₀ for acute oral toxicity is greater than 50 mg/kg but less than or equal to 500 mg/kg. 3 Materials that, under emergency conditions, can cause serious or permanent injury. Gases with an LC₅₀ for acute inhalation toxicity greater than 1,000 ppm but less than or equal to 3,000 ppm. Any liquid whose saturated vapor concentration at 20°C (68°F) is equal to or greater its LC₅₀ for acute inhalation toxicity, if its LC₅₀ is less than or equal to 3000 ppm and that does not meet the criteria for degree of hazard 4. Dusts and mists with an LC₅₀ for acute inhalation toxicity greater than 0.5 mg/L but less than or equal to 2 mg/L. Materials with an LD₅₀ for acute dermal toxicity greater than 40 mg/kg but less than or equal to 200 mg/kg. Materials that are corrosive to the respiratory tract. Materials that are corrosive to the eyes or cause irreversible corneal opacity. Materials corrosive to the skin. Cryogenic gases that cause frostbite and irreversible tissue damage. Compressed liquefied gases with boiling points below -55°C (-66.5°F) that cause frostbite and irreversible tissue damage. Materials with an LD₅₀ for acute oral toxicity greater than 5 mg/kg but less than or equal to 50 mg/kg. 4 Materials that, under emergency conditions, can be lethal. Gases with an LC₅₀ for acute inhalation toxicity less than or equal to 1,000 ppm. Any liquid whose saturated vapor concentration at 20°C (68°F) is equal to or greater than ten times its LC₅₀ for acute inhalation toxicity, if its LC₅₀ is less than or equal to 1000 ppm. Dusts and mists whose LC₅₀ for acute inhalation toxicity is less than or equal to 0.5 mg/L. Materials whose LD₅₀ for acute dermal toxicity is less than or equal to 40 mg/kg. Materials whose LD₅₀ for acute oral toxicity is less than or equal to 5 mg/kg.

FLAMMABILITY HAZARD: 0 Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand. Materials that will not burn in air when exposed to a temperature of 816°C (1500°F) for a period of 5 minutes in according with Annex D of NFPA 704. 1 Materials that must be preheated before ignition can occur. Materials in this degree require considerable preheating, under all ambient temperature conditions, before ignition and combustion can occur. Materials that will burn in air when exposed to a temperature of 816°C (1500°F) for a period of 5 minutes in according with Annex D of NFPA 704. Liquids, solids, and semisolids having a flash point at or above 93.4°C (200°F) (i.e. Class IIIB liquids). Liquids with a flash point greater than 35°C (95°F) that do not sustain combustion when tested using the *Method of Testing for Sustained Combustibility*, per 49 CFR 173, Appendix H or the UN *Recommendations on the Transport of Dangerous Goods, Model Regulations* (current edition) and the related *Manual of Tests and Criteria* (current edition). Liquids with a flash point greater than 35°C (95°F) in a water-miscible solution or dispersion with a water non-combustible liquid/solid content of more than 85% by weight. Liquids that have no fire point when tested by ASTM D 92, *Standard Test Method for Flash and Fire Points by Cleveland Open Cup*, up to the boiling point of the liquid or up to a temperature at which the sample being tested shows an obvious physical change. Combustible pellets with a representative diameter of greater than 2 mm (10 mesh). Most ordinary combustible materials. Solids containing greater than 0.5% by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent. **FLAMMABILITY HAZARD (continued): 2 (continued): 2** Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur. Materials in this degree would not under normal conditions form hazardous atmospheres with air, but under high ambient temperatures or under moderate heating could release vapor in sufficient quantities to produce hazardous atmospheres with air. Liquids having a flash point at or above 37.8°C (100°F) and below 93.4°C (200°F) (i.e. Class II and Class IIIA liquids.) Solid materials in the form of powders or coarse dusts of representative diameter between 420 microns (40 mesh) and 2 mm (10 mesh) that burn rapidly but that generally do not form explosive mixtures with air. Solid materials in fibrous or shredded form that burn rapidly and create flash fire hazards, such as cotton, sisal, and hemp. Solids and semisolids that readily give off flammable vapors. Solids containing greater than 0.5% by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent. 3 Liquids and solids that can be ignited under almost all ambient temperature conditions. Materials in this degree produce hazardous atmospheres with air under almost all ambient temperatures or, though unaffected by ambient temperatures, are readily ignited under almost all conditions. Liquids having a flash point below 22.8°C (73°F) and having a boiling point at or above 37.8°C (100°F) and those liquids having a flash point at or above 22.8°C (73°F) and below 37.8°C (100°F) (i.e. Class IB and IC liquids). Materials that on account of their physical form or environmental conditions can form explosive mixtures with air and are readily dispersed in air. Flammable or combustible dusts with representative diameter less than 420 microns (40 mesh). Materials that burn with extreme rapidity, usually by reason of self-contained oxygen (e.g. dry nitrocellulose and many organic peroxides). Solids containing greater than 0.5% by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent. 4 Materials that will rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and will burn readily. Flammable gases. Flammable cryogenic materials. Any liquid or gaseous materials that is liquid while under pressure and has a flash point below 22.8°C (73°F) and a boiling point below 37.8°C (100°F) (i.e. Class IA liquids). Materials that ignite when exposed to air. Solids containing greater than 0.5% by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent.

INSTABILITY HAZARD: 0 Materials that in themselves are normally stable, even under fire conditions. Materials that have an instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) below 0.01 W/mL. Materials that do not exhibit an exotherm at temperatures less than or equal to 500°C (932°F) when tested by differential scanning calorimetry. 1 Materials that in themselves are normally stable, but that can become unstable at elevated temperatures and pressures. Materials that have an instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) at or above 0.01 W/mL and below 10 W/mL.

DEFINITION OF TERMS (Continued)

NATIONAL FIRE PROTECTION ASSOCIATION HAZARD RATINGS (continued):

INSTABILITY HAZARD (continued): **2** Materials that readily undergo violent chemical change at elevated temperatures and pressures. Materials that have an instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) at or above 10 W/mL and below 100W/mL. **3** Materials that in themselves are capable of detonation or explosive decomposition or explosive reaction, but that require a strong initiating source or that must be heated under confinement before initiation. Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) at or above 100 W/mL and below 1000 W/mL. Materials that are sensitive to thermal or mechanical shock at elevated temperatures and pressures. **4** Materials that in themselves are readily capable of detonation or explosive decomposition or explosive reaction at normal temperatures and pressures. Materials that are sensitive to localized thermal or mechanical shock at normal temperatures and pressures. Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) of 1000 W/mL or greater.

FLAMMABILITY LIMITS IN AIR:

Much of the information related to fire and explosion is derived from the National Fire Protection Association (NFPA). **Flash Point:** Minimum temperature at which a liquid gives off sufficient vapor to form an ignitable mixture with air near the surface of the liquid or within the test vessel used. **Autoignition Temperature:** Minimum temperature of a solid, liquid, or gas required to initiate or cause self-sustained combustion in air with no other source of ignition. **LEL:** Lowest concentration of a flammable vapor or gas/air mixture that will ignite and burn with a flame. **UEL:** Highest concentration of a flammable vapor or gas/air mixture that will ignite and burn with a flame.

TOXICOLOGICAL INFORMATION:

Human and Animal Toxicology: Possible health hazards as derived from human data, animal studies, or from the results of studies with similar compounds are presented. **LD₅₀:** Lethal Dose (solids & liquids) that kills 50% of the exposed animals. **LC₅₀:** Lethal Concentration (gases) that kills 50% of the exposed animals. **ppm:** Concentration expressed in parts of material per million parts of air or water. **mg/m³:** Concentration expressed in weight of substance per volume of air. **mg/kg:** Quantity of material, by weight, administered to a test subject, based on their body weight in kg. **TDLo:** Lowest dose to cause a symptom. **TCLo:** Lowest concentration to cause a symptom. **TDo, LDLo,** and **LDo,** or **TC, TCo, LCLo,** and **LCo:** Lowest dose (or concentration) to cause lethal or toxic effects.

TOXICOLOGICAL INFORMATION (continued):

Cancer Information: **IARC:** International Agency for Research on Cancer. **NTP:** National Toxicology Program. **RTECS:** Registry of Toxic Effects of Chemical Substances. IARC and NTP rate chemicals on a scale of decreasing potential to cause human cancer with rankings from 1 to 4. Subrankings (2A, 2B, etc.) are also used. **Other Information:** **BEI:** ACGIH Biological Exposure Indices, represent the levels of determinants which are most likely to be observed in specimens collected from a healthy worker who has been exposed to chemicals to the same extent as a worker with inhalation exposure to the TLV.

REPRODUCTIVE TOXICITY INFORMATION:

A **mutagen** is a chemical that causes permanent changes to genetic material (DNA) such that the changes will propagate through generation lines. An **embryo toxin** is a chemical that causes damage to a developing embryo (i.e. within the first eight weeks of pregnancy in humans), but the damage does not propagate across generational lines. A **teratogen** is a chemical that causes damage to a developing fetus, but the damage does not propagate across generational lines. A **reproductive toxin** is any substance that interferes in any way with the reproductive process.

ECOLOGICAL INFORMATION:

EC: Effect concentration in water. **BCE:** Bioconcentration Factor, which is used to determine if a substance will concentrate in life forms that consume contaminated plant or animal matter. **TLm:** Median threshold limit. **log K_{ow}** or **log K_{oc}:** Coefficient of Oil/Water Distribution is used to assess a substance's behavior in the environment.

REGULATORY INFORMATION:

U.S.:

EPA: U.S. Environmental Protection Agency. **ACGIH:** American Conference of Governmental Industrial Hygienists, a professional association that establishes exposure limits. **OSHA:** U.S. Occupational Safety and Health Administration. **NIOSH:** National Institute of Occupational Safety and Health, which is the research arm of OSHA. **DOT:** U.S. Department of Transportation. **TC:** Transport Canada. **SARA:** Superfund Amendments and Reauthorization Act. **TSCA:** U.S. Toxic Substance Control Act. **CERCLA:** Comprehensive Environmental Response, Compensation, and Liability Act. Marine Pollutant status according to the DOT; CERCLA or Superfund; and various state regulations. This section also includes information on the precautionary warnings that appear on the material's package label.

CANADA:

WHMIS: Canadian Workplace Hazardous Materials Information System. **TC:** Transport Canada. **DSL/NDSL:** Canadian Domestic/Non-Domestic Substances List.

REVISION HISTORY

Date

January 31, 2012

December 17, 2011

Changes

Remove comma from company name.

Company name change correction. Change of heading text, Section 5. Review and up-date of exposure limits to current, Section 8. Change text on Reproductive Toxicity, Section 11. Revision to Definition of Terms. Up-date Section 12. Revise Canadian WHMIS status. Move ANSI Labeling to Section 16. Add revision history section.